

TERMINALE ELETTRONICO D440IS

ELECTRONIC INDICATOR D440IS

- **Cofano in acciaio inox** / *Stainless steel case*
- **IP54 e pannello IP65** / *IP54 case, IP65 front panel*
- **Display grafico retroilluminato 135x32mm** / *Backlit graphic display 135x32 mm*
- **Tastiera a membrana a 18 tasti** / *18-key alphanumeric membrane keyboard*
- **Nr. 2 uscite seriali configurabili** / *No. 2 RS232/RS422 configurable serial ports*
- **Nr. 4 Inputs / Outputs** / *No. 4 Inputs / Outputs*
- **Atex zone 1, 21, 2, 22** / *Atex zone 1, 21, 2, 22*



Codice Code	Descrizione Description
T00174	D440IS con alimentatore 230 Vac / D440IS with 230 Vac power supply
T00175	D440IS con alimentatore 115 Vac / D440IS with 115 Vac power supply
T00268	D440IS con alimentatore 230 Vac + nr.3 Outputs Exi / D440IS with 230 Vac power supply + no.3 Exi Outputs
T00269	D440IS con alimentatore 115 Vac + nr.3 Outputs Exi / D440IS with 115 Vac power supply + no.3 Exi Outputs

Options	
OC0632	Kit per fissaggio a parete / <i>Wall mounting kit</i>
OC0630	Scheda 4-20mA / 0-10V / 4-20mA / 0-10V card
OC0631	Scheda con uscita in fibra ottica / <i>Optical fiber output card</i>
8S	MPP alibi memory / <i>MPP alibi memory</i>

