

TERMINALE INOX TOUCH SCREEN FLYNET50i

TOUCH SCREEN S. STEEL INDICATOR FLYNET50i

- **Display a colori 5,7" touch screen /**
5,7" touch screen colour display
- **Case in acciaio inox Aisi 304 /**
Aisi 304 stainless steel enclosure
- **IP68 / IP69K /**
IP68 / IP69K
- **Data Base SQL / SQL data-base**
- **Esportazione file CSV via rete, USB /**
Exporting CSV files through network, USB
- **Archiviazione pesate in PDF /**
Weighing operations archiving in PDF format
- **Alimentazione 12Vdc / Power supply 12V**



Codice Code	Descrizione Description
T00430	FLYNET50 inox con pressacavi / Kit per fissaggio a parete incluso / Stainless steel FLYNET50 with cable glands/Wall mounted kit included
	Options
OC1964	Kit da tavolo / Table Kit
OC2574	Gateway PROFINET (esterno) / Gateway PROFINET
OC2737	Scheda 8 Inputs / 12 Outputs / 8 Inputs / 12 Outputs card
OC1647	Morsettiera per scheda 8 Inputs / 12 Outputs / Indicator block for 8 Inputs / 12 Outputs card
OC0984	Scheda 4-20mA / 0-10V, nr. 2 ingressi contaimpulsi 2Khz / 4-20mA / 0-10V card, no.2 pulse counter inputs 2Khz
OC0985	Scheda WIFI esterna / External WIFI card
OC1077	MPP alibi memory / MPP alibi memory
OC1648	Software per Stampa in formato A4 e PDF / A4 and PDF print software

Caratteristiche tecniche / Specifications

Alimentazione / Power supply	12Vdc - 5A / 12Vdc - 5A
Processore / Processor	1 Ghz, 512 Mbyte RAM, 1 Gbyte flash memory / 1 Ghz, 512 Mbyte RAM, 1 Gbyte flash memory
Display / Display	Touch screen 5,7" a colori, tecnologia TFT, backlight a led / 5.7" Touch screen colour display, TFT technology, LED backlit

Porte di comunicazione / Communication ports

Ethernet 10/100 MBps / Ethernet 10/100 MBps
Nr. 1 Uscita HDMI opzionale / No. 1 HDMI optional
Nr. 4 porte USB host / No. 4 USB host ports
Nr. 3 uscite seriali RS232/RS422 / No. 3 RS232/RS422 serial outputs
Nr. 2 slots per espansioni: seriali, I/O digitali, Bus di campo, I/O analogici / No. 2 expansions slots: serial, digital I/O, field bus, analogue I/O


TERMINALE INOX TOUCH SCREEN FLYNET50i

TOUCH SCREEN S. STEEL INDICATOR FLYNET50i

Bilance / Scales

Nr. Bilance collegabili / No. of connectable scales	Fino a nr. 2 bilance analogiche o digitali / Up to no. 2 analogue or digital scales
Max. nr. di celle analogiche / Max. no. of anal. load cells	12 celle 350 ohm (12 + 12 per la versione duplex) / 12 load cells 350 ohm (12 + 12 for duplex version)
Omologazione / Display	Approvazione CE fino a 6000 divisioni, Multirange: 3x3000 o 2x4000 / CE approval up to 6000 divisions, Multirange: 3x3000 or 2x4000
Alimentazione celle di carico / Load cells power supply	Celle analogiche: 5Vdc, celle digitali 10-18Vdc / Analogue load cell: 5Vdc, digital load cell 10-18Vdc
Convertitore A/D / A/D convertor	Sigma Delta 24 bits, filtri digitali, alim. 5Vdc, 6 fili (sensing alim. celle) / Sigma Delta 24 bits, digital filtering, 5Vdc power supply, 6-wire connection

Versione da tavolo / Tabletop versin



Fissaggio a parete / Wall mounting

